



## VC-BC301P

### 4K IP POV Camera



The Lumens® VC-BC301P is a 4K Ultra-HD IP POV camera built with a 1/1.8-inch high sensitive sensor that delivers an ultra-clear and crisp image at 60fps. It supports the following features 102° wide viewing angle, tally light, and PoE. With its robust and compact design, the VC-BC301P can be integrated into any environment including broadcasting, houses of worship, e-sports, and conference halls.

## Key Features

- High Quality 4K 60fps Images
- Compact Design with Tally Light
- 102° Wide Viewing Angle
- HDMI, Ethernet, and USB3.0 Video Outputs

## Key Feature Details



### Crystal-Clear Image Quality

VC-BC301P is built with a 1/1.8-inch high sensitive sensor that delivers an ultra-clear and crisp image at 4K 60fps.



### Built-in Tally Light

The tally light turns on when the camera is in operation. The robust and compact design allows an easy installation process.



### Wide Viewing Angle

The 102 degrees horizontal viewing angle enlarges the flexibility of the video production. Ensure everyone is visible in the frame.



### PoE

Power is supplied through the PoE (Power over Ethernet) without additional power supply and cables that bring cost-effective and simple installation.

# Applications



House of Worship



Live Events



E-sports

## Product Specifications


<b>Sensor</b>	1/1.8" 9.17 MP CMOS
<b>Video Format</b>	Resolution : 4K / 1080p / 720p Frame Rate : 59.94 / 50 / 29.97 / 25
<b>Video Output (HD) Interface</b>	HDMI 2.0, Ethernet, USB 3.0 (USB 2.0 compatible)
<b>Pixel Zoom</b>	2x for 1080p (1920x1080) 3x for 720p (1280x720)
<b>Digital Zoom</b>	12x
<b>Horizontal Viewing Angle</b>	102°
<b>PTZ</b>	ePTZ
<b>Aperture</b>	F1.6
<b>Focal Length</b>	4.57 mm
<b>Shutter Speed</b>	1 ~ 1/10,000 sec
<b>Minimum Object Distance</b>	30 cm
<b>Video S/N Ratio</b>	> 50dB
<b>Minimum Illumination</b>	0.05 lux (F1.6, 50IRE, 30fps)
<b>Focus System</b>	Manual
<b>Gain Control</b>	Auto / Manual
<b>White Balance</b>	Auto / Manual
<b>Exposure Control</b>	Auto / Manual

<b>WDR</b>	Yes
<b>3D NR</b>	Yes
<b>Image Flip</b>	Yes
<b>Preset Positions</b>	256
<b>Multiple Video Stream</b>	HEVC 4K 59.94fps H.264 1080p 59.94fps H.264 640x360 29.97fps
<b>Audio Compression Format</b>	G.711 / AAC
<b>Control Interface</b>	Ethernet / USB
<b>Control Protocol</b>	VISCA over IP / ONVIF / UVC
<b>Tally Light</b>	Yes
<b>PoE</b>	PoE (IEEE802.3af)
<b>Video Stream</b>	RTSP / RTMP / RTMPS / MPEG-TS / SRT
<b>Video Compression</b>	HEVC / H.264 / MJPEG
<b>Audio In</b>	Line In / Mic In (Phone Jack 3.5mm x1)
<b>DC In</b>	12V +/- 20%
<b>Power Consumption</b>	PoE : 11W DC In : 10W
<b>Weight</b>	0.77lbs (350g)
<b>Dimensions</b>	4.4" x 2.8" x 2.0" (113 x 70 x 51 mm)

## Compatible Software



## User Interface



# Lumens®

Lumens Integration, Inc.  
4116 Clipper Court  
Fremont, CA, 94538  
Phone: +1-866-600-0988  
Fax: +1-510-252-1389

Lumens Europe  
De Nayerstraat 17 9470  
Denderleeuw Belgium  
Phone : +32-473-58-38-95  
Fax : +32-2-452-76-00



www.MyLumens.com