

# 3733

## Three-Way Bi-Amplified ScreenArray® Cinema Loudspeakers



### Key Features:

- Three-way ScreenArray® design for maximum output, optimal coverage and minimum distortion
- Dual Dissimilar Arraying technology to improve high frequency coverage in rooms with raked seating
- JBL 2415-XP next-generation high frequency compression driver
- Advanced waveguide design for improved frequency response and higher output with lower distortion
- Used in conjunction with CRF2 reflector horns, which are used to reflect high frequency content off a solid screen
- Includes the same HF driver as the CRF2 to maintain tonal quality
- Supports bi-amp configuration only



Front



Rear

### Description:

For critical sound reproduction in cinemas utilizing a solid screen. The 3733 uses the 4739 LF for increased low frequency output. The M/HF utilizes Dual Dissimilar Arraying technology to optimize the coverage pattern for rooms with raked seating. In addition, the horn design improves the frequency response and lowers distortion at higher output levels. The 2415-XP high frequency drivers represent JBL's latest HF compression driver, designed to achieve higher output with lower harmonic distortion.

### Specifications:

System	
Frequency Response (-3 dB)	40Hz – 19kHz
System Input Power Handling	LF: 800 W, M/HF: 300 W
Horizontal Coverage Angle (-6dB)	100°
Vertical Coverage Angle (-6dB)	Asymmetrical with Dual Dissimilar Arraying
Net Weight	71.8 kg (158 lb)
Shipping Weight	86.7 kg (191 lb)
Dimension (H x W x D)	1000 mm x 1648 mm x 450 mm (39.37 in x 64.88 in x 17.75 in)

LF Component Electronics – Model 4739	
Low Frequency Transducers	2 x 265H-2, 380mm (15 in dia.), Differential Drive® edgewood ribbon voice coil transducers mounted in 4509 enclosure
Nominal Impedance	4 ohms
Input Power Handling	800 W, 1200 W recommended amplifier
Free-Field Sensitivity	104 dB, 2.83V @ 1m (3.3 ft)
Dimensions (H x W x D)	883 mm x 762 mm x 450 mm (34.75 in x 30 in x 17.75 in)
Net Weight	48.6 kg (107 lb)
Shipping Weight	55.4 kg (122 lb)

M/HF Component Electronics – Model 3733 M/HF	
Mid Frequency Transducers	2 x 165H, 165 mm (6.5 in) diameter, 38 mm (1.5 in) voice coil
High Frequency Transducers	2 x 2415-XP, Dual Dissimilar Arraying configuration
Nominal Impedance	12 ohms
Minimum Impedance	10.2 ohms @ 12 kHz
Free-Field Sensitivity	104 dB, 2.83 V @ 1m (3.3 ft)
Input Power Handling (AES 100-Hour Rating)	150 W (39.1 V)
Input Power Handling (AES 2-Hour Rating)	200 W (45.2 V)
Dimensions (H x W x D)	1000 mm x 762 mm x 450 mm (39.37 in x 30 in x 17.75 in)
Net Weight	23.2 kg (51 lb)
Shipping Weight	31.3 kg (69 lb)

Specifications are stated in free-field (4pi) conditions.

JBL continually engages in research related to product improvement. Some materials, production methods and design refinements are introduced into existing products without notice as a routine expression of that philosophy. For this reason, any current JBL product may differ in some respect from its published description, but will always equal or exceed the original design specifications unless otherwise stated.