PSR7-V Versatile Mount 5.5 Amp Power Supply

PSR7-V (FG423-49)

Overview

The PSR7-V power supply provides 5.5 amps of 12VDC power and is an optional power supply for Modero® X Series line of touch panels and NetLinx NX Integrated Central Controllers. It includes three 3.5 mm phoenix connectors with retention screws.

Accessories include a V-style module rack tray and surface mount brackets which allow the PSR7-V power supply to be securely mounted to flat surfaces such as under a table or on a wall. Up to three power supplies can be mounted side-by-side using a 1 RU space.

Common Applications

Ideal for professional AV installations, the PSR7-V power supply helps to protect valuable components against over-voltage, over-current, short-circuit, transient and thermal damage.

Features

- **Protection** – Against over-voltage, over-current, short-circuit, transient and thermal; switching regulated and overload protected.
- **Power Indicator** – Green LED indicates DC on the output in fault tolerant range.
- **Connectors** – Includes 3x mini 2-pin captive wire connector (3.5 mm).
- **Input Power Cord** – IEC power cord provided as a separate part, dependent on country requirements.

Specifications

POWER SUPPLY	
Input Voltage	~100-240 V, 1.9A MAX, 47/63 Hz
Output Voltage	12 VDC +/-.6V
Output Current	5.5 A

DIMENSIONS	
Dimensions	1 5/8" x 5 3/4" x 5 1/8" (4.13 cm x 14.6 cm x 13.02 cm) (HWD)

WEIGHT	
Input Voltage	1.45 lb. (657 g)

OPERATING ENVIRONEMENT	
Operating Temp.	32°F to 122°F (0°C to 50°C)
Storage Temp.	-4°F to 176°F (-20°C - 80°C)

Certifications	
Certifications	• UL/cUL/CB • UL AR • UL, RCM -Australia, New Zealand • UL - Morocco • NOM - Mexico • FCC Part 15 Subpart B • CCC - China